# SAFETY DATA SHEET

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

VANILLA CUSTARD FLAVOR ART

of the mixture

Registration number

Synonyms None.

Product code CA1038

Issue date 02-September-2015

Version number 07

**Revision date** 15-February-2017 **Supersedes date** 07-November-2016

1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses**Use in accordance with supplier's recommendations.

Uses advised against No other uses are advised.

1.3. Details of the supplier of the safety data sheet

Supplier

Company name Capella Flavors, Inc.
Address 6155 Corte Del Cedro

Carlsbad, CA 92011

United States

**Division** 

**Telephone** Office 760 650-0200

Fax n/a

e-mail customerservice@capellaflavors.com

Contact person Not available.

**1.4. Emergency telephone** CHEMTREC 800-424-9300

number

INTERNATIONAL 703-741-5500

# **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

### Classification according to Regulation (EC) No 1272/2008 as amended

**Health hazards** 

Serious eye damage/eye irritation Category 2 H319 - Causes serious eye

irritation.

Skin sensitisation Category 1B H317 - May cause an allergic skin

reaction.

**Hazard summary**Causes serious eye irritation. May cause irritation to the respiratory system. May cause an allergic

skin reaction. Occupational exposure to the substance or mixture may cause adverse health

effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: PENTANEDIONE,2,3 (ACETYL PROPIONYL) #205, TRADE SECRET

Hazard pictograms

♦

Signal word Warning

**Hazard statements** 

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

Material name: VANILLA CUSTARD FLAVOR ART - Capella Flavors, Inc.

CA1038 Version #: 07 Revision date: 15-February-2017 Issue date: 02-September-2015

#### **Precautionary statements**

_				
- 0	rev	101	nti	n

Avoid breathing mist or vapour. P261 Wash thoroughly after handling. P264

Contaminated work clothing should not be allowed out of the workplace. P272

Wear eye protection/face protection. P280

Wear protective gloves. P280

Response

IF ON SKIN: Wash with plenty of water. P302 + P352

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present P305 + P351 + P338

and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. P333 + P313 If eye irritation persists: Get medical advice/attention. P337 + P313 Take off contaminated clothing and wash it before reuse. P362 + P364

Storage Store away from incompatible materials.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations. P501

#### Supplemental label information None

#### 2.3. Other hazards

Not a PBT or vPvB substance or mixture. This product contains a butter flavoring other than diacetyl. The health effects of these materials are currently being studied for potential respiratory hazards. Avoid eye contact or breathing dust, powder, mist or vapor from this product as irritation of the eyes or respiratory tract may result. This product contains ingredients for which the health effects have not been fully evaluated.

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

#### **General information**

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
VANILLIN #234	5 - < 10	121-33-5 204-465-2	-	-	
Classification:	Eye Irrit. 2;H319				
ETHYL MALTOL NOM #	<del>1</del> 169 3-<5	4940-11-8 225-582-5	-	-	
Classification:	Acute Tox. 4;H302				
ETHYL VANILLIN #296	3-<5	121-32-4 204-464-7	-	-	
Classification:	Eye Irrit. 2;H319				
PENTANEDIONE,2,3 (AC PROPIONYL) #205	ETYL 1-<3	600-14-6 209-984-8	-	-	
Classification:	Flam. Liq. 2;H225, Skin	Sens. 1B;H317, E	ye Dam. 1;H318, STOT RE 2;H3	373	
TRADE SECRET	< 0,2	Proprietary -	-	-	
Classification:	Acute Tox. 4;H302, Skir	n Sens. 1B;H317, E	ye Dam. 1;H318		

Other components below reportable levels 80 - < 90

### List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

The full text for all H-statements is displayed in section 16. **Composition comments** 

#### **SECTION 4: First aid measures**

Ensure that medical personnel are aware of the material(s) involved, and take precautions to **General information** 

protect themselves. Wash contaminated clothing before reuse.

#### 4.1. Description of first aid measures

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing Inhalation

respiratory symptoms: Call a POISON CENTRE or doctor/physician.

**Skin contact** Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

**Ingestion** Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and

delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision. May cause an allergic skin reaction. Dermatitis. Rash.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

# **SECTION 5: Firefighting measures**

General fire hazards No unusual fire or explosion hazards noted.

5.1. Extinguishing media

Suitable extinguishing

media

Unsuitable extinguishing

media

During fire, gases hazardous to health may be formed.

Alcohol resistant foam. Powder. Carbon dioxide (CO2).

5.2. Special hazards arising from the substance or mixture

5.3. Advice for firefighters

Special protective equipment for firefighters

Special fire fighting procedures

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Move containers from fire area if you can do so without risk.

Do not use water jet as an extinguisher, as this will spread the fire.

**Specific methods**Use standard firefighting procedures and consider the hazards of other involved materials.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapour, fumes, dust and/or mist from the spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

For emergency responders

Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

SDS

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Avoid discharge into drains, water courses or onto the ground. Use water spray to reduce vapours or divert vapour cloud drift.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

## **SECTION 7: Handling and storage**

7.1. Precautions for safe handling

Avoid breathing mist or vapour. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store in a well-ventilated place. Store

away from incompatible materials (see Section 10 of the SDS).

7.3. Specific end use(s) Not available.

# **SECTION 8: Exposure controls/personal protection**

8.1. Control parameters

SDS EU

# Occupational exposure limits

RROPYLENE GLYCOL NOM NFI (CAS 57-55-6)   MAC   10 mg/m3   150 ppm   150 pp	Components	ce Exposure Limit Values in the Workpla Type	Value	arourie Noville, 13/09		
Incland. Occupational Exposure Limits Components  Type  TWA  A70 mg/m3 10 mg/m3 1150 ppm 1150		MAC	10 mg/m3			
Components         Type         Value         Form           PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)         TWA         470 mg/m3         Total vapour and particulates. Particulate. Particulate. Particulates.           Latvia. OELs. Occupational exposure limit values of chemical substances in work environment Components         Type         Value           PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)         TWA         7 mg/m3         TWA           Littuania. OELs. Limit values for Chemical Substances, General Requirements         Components         Value           PROPYLENE GLYCOL Components         TWA         7 mg/m3           NOM NFI (CAS 57-55-6)         TWA         7 mg/m3           VARY Components         Type         Value           PROPYLENE GLYCOL NOWN NFI (CAS 57-55-6)         TLV         79 mg/m3           VOM NFI (CAS 57-55-6)         TLV         79 mg/m3           VAIUE PROPYLENE GLYCOL NOWN NFI (CAS 57-55-6)         TLV         79 mg/m3           VAIUE PROPYLENE GLYCOL NOWN NFI (CAS 57-55-6)         TWA         474 mg/m3         Total vapour and particulates.           VAIUE PROPYLENE GLYCOL NOWN NFI (CAS 57-55-6)         No biological exposure limits noted for the ingredient(s).         Total vapour and particulates.           VAIUE PROPYLENE GLYCOL NOWN NFI (CAS 57-55-6)         No tavailable.         No tavailable.           Components<	NOW NIT (CAS 31-33-0)		150 ppm			
PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)  TWA  470 mg/m3 10 mg/m3 150 ppm 150 pp				_		
NOM NFI (CAS 57-55-6)  Latvia. OELs. Occupational exposure limit values of chemical substances in work environment Components  Type  TWA  Typin3  NOM NFI (CAS 57-55-6)  Littuania. OELs. Limit values for Chemical Substances, General Requirements Components  Type  PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)  Littuania. OELs. Limit values for Chemical Substances, General Requirements Components  Type  PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)  TWA  Type  Value  PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)  TLV  Type  Value  PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)  TLV  Type  Value  PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)  UK. EH40 Workplace Exposure Limits (WELs) Components  Type  Value  PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)  UK. EH40 Workplace Exposure  Limits (WELs) Type  Value  PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)  UK. EH40 Workplace Exposure  Limits (WELs) Type  Value  Form  PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)  UK. EH40 Workplace Exposure  Limits (WELs) Type  Value  Form  PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)  UK. EH40 Workplace Exposure  Limits (WELs) Type  Value  Form  Total vapour and particulates. Particulate	Components	Туре	Value	Form		
Latvia. OELs. Occupational exposure limit values of chemical substances in work environment Components Type Value  PROPYLENE GLYCOL NOM NFI (CAS 57-56-6) TWA TMA Tmg/m3  PROPYLENE GLYCOL NOM NFI (CAS 57-56-6) TWA Thype Value  PROPYLENE GLYCOL NOM NFI (CAS 57-56-6) TUV Type Value  PROPYLENE GLYCOL NOM NFI (CAS 57-55-6) TuV Type Value  PROPYLENE GLYCOL NOM NFI (CAS 57-55-6) TuV Type Value  PROPYLENE GLYCOL NOM NFI (CAS 57-55-6) TuV Type Value  PROPYLENE GLYCOL NOM NFI (CAS 57-55-6) TuV Type Value Total vapour and particulates. Total vap		TWA	470 mg/m3			
Lativia. OELs. Occupational exposure limit values of chemical substances in work environment Components Type Value  PROPYLENE GLYCOL NOM NFI (CAS 57-55-6) Lithuania. OELs. Limit Values for Chemical Substances, General Requirements Components Type Value  PROPYLENE GLYCOL NOM NFI (CAS 57-55-6) NOM NFI (CAS 57			_	Total vapour and		
PROPYLENG ELYCOL NOM NFI (CAS 57-55-6)	Latvia OFLs Occupational e	exposure limit values of chemical substa	ances in work environment	particulates.		
NOM NFI (CAS 57-55-6) Lithuania. OELs. Limit Values for Chemical Substances, General Requirements Components Type Value  PROPYLENE GLYCOL NOM NFI (CAS 57-55-6) Norway. Administrative Norms for Contaminants in the Workplace Components Type Value  PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)  ROPPLENE GLYCOL NOM NFI (CAS 57-55-6)  UK. EH40 Workplace Exposure Limits (WELs) Components Type Value PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)  TWA 474 mg/m3 Total vapour and particulates. 100 mg/m3 Particulates. 1150 ppm Total vapour and particulates. 150 ppm Total vapour and p	Components					
PROPYLENE GLYCOL NOM NFI (CAS 57-55-6) Norway, Administrative Norms for Contaminants in the Workplace Components Type Value PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)  UK. EH40 Workplace Exposure Limits (WELs) Components Type Value PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)  TWA  474 mg/m3 Particulates Particulates Particulates Particulates Particulates Particulates Particulates Particulates Propriate application Propriate engineering Office time the propriate engineering Office time the propriate engineering Office time the propriate engineering or trotter engineering or trotte or engineering or trotte to the propriate engineering or trotte or engineering or trotte to the propriate engineering or trotte to the propriate engineering or trotte to the propriate exposure limits in airborne levels below recommended exposure limits. If exposure process enclosures, local exhaust ventiliation, or other engineering or trottes to maintain airborne levels below recommended exposure limits. If exposure process enclosures, local exhaust ventiliation, or other engineering or trottes to maintain airborne levels below recommended exposure limits. If exposure process enclosures, local exhaust ventiliation, or other engineering or trottes to engineering or trottes below recommended exposure limits. If exposure process enclosures, local exposure		TWA	7 mg/m3			
PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)  Norway, Administrative Norms for Contaminants in the Workplace Components  Type  PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)  UK. EH40 Workplace Exposure Limits (WELs) Components  Type  Value  PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)  UK. EH40 Workplace Exposure Limits (WELs) Components  Type  Value  Form  PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)  UK. EH40 Workplace Exposure Limits (WELs) Components  Type  Value  Form  PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)  NOM NFI (CAS 57-55-6)  Total vapour and particulates. 10 mg/m3 Particulates. 150 ppm Total vapour and particu		·	-			
NOM NFI (CAS 57-55-6)  Norway, Administrative Norms for Contaminants in the Workplace Components  Type Value  PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)  UK. EH40 Workplace Exposure Limits (WELs) Components  Type Value  PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)  Type Value  From  Type Value Form  Total vapour and particulates. 10 mg/m3 particulates.						
PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)		TWA	7 mg/m3			
PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)  UK. EH40 Workplace Exposure Limits (WELs) Components  Type  Value  Form  PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)  NOM NFI (CAS 57-55-6)  PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)  NO biological exposure limits noted for the ingredient(s).  Total vapour and particulates.  10 mg/m3 Particulate.  150 ppm Total vapour and particulates.  Propriate and particulates.  Not available.  Follow standard monitoring procedures.  Follow standard monitoring procedures.  Formended monitoring procedures.  Follow standard monitoring procedure		<del>-</del>	W.L.			
UK. EH40 Workplace Exposure Limits (WELs) Components  Type  Value  Form  PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)  ROBINATION OF I (CAS 57-55-1-1)  ROBINATION OF I (CAS 57-5-1-1)  ROBINATION OF I (CAS 57-5-1-1)  ROBINAT	Components	<u> </u>	Value			
UK. EH40 Workplace Exposure Limits (WELs) Components  Type  Value  Form  Type  Value  Form  Total vapour and particulates. Particulate.		TLV	79 mg/m3			
PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)   TWA 474 mg/m3 particulates.   Total vapour and particulates.   10 mg/m3 particulates.   10 mg/m3 particulates.   10 mg/m3 particulates.   150 ppm   Total vapour and particulates.   150 ppm   Total			25 ppm			
NOM NFI (CAS 57-55-6)  Nome and particulates.  10 mg/m3 Particulates. 150 ppm Total vapour and p			Value	Form		
logical limit values commended monitoring codures commended monitoring codures codures commended monitoring codures co		TWA	•			
No biological exposure limits noted for the ingredient(s). Follow standard monitoring procedures.  Not available.  Not available.  Itels)  Not available.  Respiratory protection  Not available.  Not availab			•	Total vapour and		
Follow standard monitoring procedures.  ived no effect levels IELs)  dicted no effect Incentrations (PNECs)  Exposure controls  or opriate engineering Introls  Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.  ividual protection measures, such as personal protective equipment  General information  Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.  Eye/face protection  Face shield is recommended. Wear safety glasses with side shields (or goggles).  Skin protection  Hand protection  Wear appropriate chemical resistant gloves.  Other  Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.  In case of insufficient ventilation, wear suitable respiratory equipment.	logical limit values	No biological exposure limits noted fo	or the ingredient(s).	partiodiatoo.		
Not available.  dicted no effect propriate engineering partials  As personal protective equipment  General information  Use personal protective equipment  Beyelface protection  Face shield is recommended. Wear safety glasses with side shields (or goggles).  Skin protection  Hand protection  Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.  Not available.	ommended monitoring	Follow standard monitoring procedure				
Exposure controls  Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.  ividual protection measures, such as personal protective equipment  General information  Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.  Eye/face protection  Face shield is recommended. Wear safety glasses with side shields (or goggles).  Skin protection  Hand protection  Wear appropriate chemical resistant gloves.  Other  Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.  In case of insufficient ventilation, wear suitable respiratory equipment.	ived no effect levels	Not available.				
Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.  Ividual protection measures, such as personal protective equipment  General information  Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.  Eye/face protection  Face shield is recommended. Wear safety glasses with side shields (or goggles).  Skin protection  Hand protection  Wear appropriate chemical resistant gloves.  Other  Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.  In case of insufficient ventilation, wear suitable respiratory equipment.		Not available.				
should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.  Ividual protection measures, such as personal protective equipment  General information  Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.  Eye/face protection  Face shield is recommended. Wear safety glasses with side shields (or goggles).  Skin protection  Hand protection  Wear appropriate chemical resistant gloves.  Other  Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.  In case of insufficient ventilation, wear suitable respiratory equipment.	Exposure controls					
General informationUse personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.Eye/face protectionFace shield is recommended. Wear safety glasses with side shields (or goggles).Skin protectionWear appropriate chemical resistant gloves OtherWear appropriate chemical resistant clothing. Use of an impervious apron is recommended.Respiratory protectionIn case of insufficient ventilation, wear suitable respiratory equipment.	•	should be matched to conditions. If a or other engineering controls to maint exposure limits have not been establi	pplicable, use process enclosure tain airborne levels below recom	es, local exhaust ventilation, imended exposure limits. If		
according to the CEN standards and in discussion with the supplier of the personal protective equipment.  Eye/face protection  Skin protection  - Hand protection  Wear appropriate chemical resistant gloves.  Other  Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.  Respiratory protection  In case of insufficient ventilation, wear suitable respiratory equipment.	vidual protection measures, s	uch as personal protective equipment				
Skin protection - Hand protection - Other  Wear appropriate chemical resistant gloves.  Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.  Respiratory protection  In case of insufficient ventilation, wear suitable respiratory equipment.	General information	according to the CEN standards and				
<ul> <li>- Hand protection Wear appropriate chemical resistant gloves.</li> <li>- Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.</li> <li>Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.</li> </ul>	Eye/face protection	Face shield is recommended. Wear s	afety glasses with side shields (	(or goggles).		
<ul> <li>- Hand protection Wear appropriate chemical resistant gloves.</li> <li>- Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.</li> <li>Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.</li> </ul>	Skin protection					
- Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.  Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.	-	Wear appropriate chemical resistant (	gloves.			
	- Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.				
	Respiratory protection	In case of insufficient ventilation. wea	In case of insufficient ventilation, wear suitable respiratory equipment.			
	• •	·				

Material name: VANILLA CUSTARD FLAVOR ART - Capella Flavors, Inc.

CA1038 Version #: 07 Revision date: 15-February-2017 Issue date: 02-September-2015

**Hygiene measures** Always observe good personal hygiene measures, such as washing after handling the material

and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the

workplace.

**Environmental exposure** 

Environmental manager must be informed of all major releases.

controls

# **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

**Appearance** 

Physical stateLiquid.FormLiquid.ColourNot available.

OdourNot available.Odour thresholdNot available.pHNot available.

Melting point/freezing point -59 °C (-74,2 °F) estimated
Initial boiling point and boiling 188,2 °C (370,76 °F) estimated

range

Flash point 92,3 °C (198,1 °F)
Evaporation rate Not available.
Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper Not available.

(%)

Vapour pressure 0,15 hPa estimated

Vapour density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

**Auto-ignition temperature** 371,11 °C (700 °F) estimated

Decomposition temperatureNot available.ViscosityNot available.Explosive propertiesNot explosive.Oxidising propertiesNot oxidising.

9.2. Other information

 Refractive index
 1,434 - 1,464

 Specific gravity
 1,04 - 1,08

### **SECTION 10: Stability and reactivity**

**10.1. Reactivity** The product is stable and non-reactive under normal conditions of use, storage and transport.

**10.2. Chemical stability**Material is stable under normal conditions.

**10.3. Possibility of hazardous** No dangerous reaction known under conditions of normal use.

reactions

**10.4. Conditions to avoid** Avoid temperatures exceeding the flash point. Contact with incompatible materials.

**10.5. Incompatible materials** Strong oxidising agents.

**10.6. Hazardous** No hazardous decomposition products are known.

decomposition products

#### **SECTION 11: Toxicological information**

**General information** Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

**Inhalation** May cause irritation to the respiratory system. Prolonged inhalation may be harmful.

**Skin contact** May cause an allergic skin reaction.

Material name: VANILLA CUSTARD FLAVOR ART - Capella Flavors, Inc.

Eye contact Causes serious eye irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred **Symptoms** 

vision. May cause an allergic skin reaction. Dermatitis. Rash.

11.1. Information on toxicological effects

No data available. Acute toxicity

Due to partial or complete lack of data the classification is not possible. Skin corrosion/irritation Causes serious eye irritation.

Serious eye damage/eye

Respiratory sensitisation

irritation

Due to partial or complete lack of data the classification is not possible.

May cause an allergic skin reaction. Skin sensitisation

Germ cell mutagenicity Due to partial or complete lack of data the classification is not possible. Due to partial or complete lack of data the classification is not possible. Carcinogenicity

Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work

(as amended)

Not listed.

Reproductive toxicity Specific target organ toxicity -

single exposure

Due to partial or complete lack of data the classification is not possible. Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

repeated exposure **Aspiration hazard** 

Due to partial or complete lack of data the classification is not possible.

Due to partial or complete lack of data the classification is not possible.

Mixture versus substance

information

No information available.

Other information Not available.

**SECTION 12: Ecological information** 

12.1. Toxicity Based on available data, the classification criteria are not met for hazardous to the aquatic

environment.

12.2. Persistence and

degradability

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

> ETHYL VANILLIN #296 1,61 VANILLIN #234 1,37

**Bioconcentration factor (BCF)** Not available. No data available. 12.4. Mobility in soil

Not a PBT or vPvB substance or mixture. 12.5. Results of PBT

and vPvB assessment

12.6. Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

**SECTION 13: Disposal considerations** 

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

EU waste code The Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of Disposal methods/information

contents/container in accordance with local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. **Special precautions** 

CA1038

Material name: VANILLA CUSTARD FLAVOR ART - Capella Flavors, Inc.

#### **SECTION 14: Transport information**

ADR

14.1. - 14.6.: Not regulated as dangerous goods.

RID

14.1. - 14.6.: Not regulated as dangerous goods.

**ADN** 

14.1. - 14.6.: Not regulated as dangerous goods.

IATA

14.1. - 14.6.: Not regulated as dangerous goods.

**IMDG** 

14.1. - 14.6.: Not regulated as dangerous goods.

14.7. Transport in bulk Not established.

according to Annex II of Marpol

and the IBC Code

# **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **EU regulations**

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I, as amended

Not listed.

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex II, as amended

Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

**Authorisations** 

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Not listed

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at

work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed.

Other regulations The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP

Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended. Additional information is given in the Safety Data Sheet.

National regulations Follow national regulation for work with chemical agents. Young people under 18 years old are not

allowed to work with this product according to EU Directive 94/33/EC on the protection of young

people at work, as amended.

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

# **SECTION 16: Other information**

List of abbreviations Not available.

References Not available.

Information on evaluation method leading to the classification of mixture Full text of any H-statements not written out in full under

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure by inhalation.

This document has undergone significant changes and should be reviewed in its entirety.

Follow training instructions when handling this material.

Capella Flavors, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

**Revision information Training information** Disclaimer

Sections 2 to 15

Material name: VANILLA CUSTARD FLAVOR ART - Capella Flavors, Inc.

Version #: 07 Revision date: 15-February-2017 Issue date: 02-September-2015 CA1038